



3 ROLLS PLATE BENDING MACHINE WITH VARIABLE GEOMETRY SERIES E79 TECHNICAL SPECIFICATION

SERIES	MODELL	TABLE WIDTH (mm)	Ø TOP ROLL (mm)	Ø BOTTOM ROLLS (mm)	CAPACITY CALCULATED WITH PLATE YIELD POINT 260 N/mm ²				WEIGHT (TON)
					PRE-PINCHING x 1,5 TR	PRE-PINCHING x 5 TR	ROLLING x 1,5 TR	ROLLING x 5 TR	
E79	1634	1600	340	310	26	30	41	44	12
E79	1638	1600	380	330	36	40	48	52	16
E79	1649	1600	490	440	50	55	65	72	23
E79	1653	1600	530	450	75	80	83	93	33
E79	1658	1600	580	470	92	102	99	109	48
E79	1665	1600	650	520	120	135	127	142	78
E79	1675	1600	750	610	145	155	152	170	70
E79	2136	2100	360	320	24	28	36	39	14
E79	2140	2100	400	350	32	36	44	48	18
E79	2151	2100	510	460	45	50	58	63	30
E79	2155	2100	550	470	64	69	73	80	39
E79	2160	2100	600	490	75	82	86	95	61
E79	2168	2100	680	550	100	110	115	123	75
E79	2177	2100	770	630	125	140	138	153	81
E79	2638	2600	380	330	22	26	33	36	15
E79	2642	2600	420	370	28	32	40	44	20
E79	2653	2600	530	480	40	45	52	57	34

E79	2657	2600	570	490	54	60	67	72	43
E79	2662	2600	620	510	65	70	78	85	63
E79	2672	2600	720	620	90	96	100	110	86
E79	2679	2600	790	650	105	117	125	137	90
E79	3140	3100	400	350	20	24	29	33	17
E79	3145	3100	450	390	24	30	36	40	21
E79	3155	3100	550	490	35	40	48	53	36
E79	3162	3100	620	520	48	52	61	67	48
E79	3167	3100	670	560	60	65	71	78	65
E79	3175	3100	750	640	80	85	93	101	95
E79	3185	3100	850	680	100	108	115	126	120
E79	3642	3600	420	370	18	21	27	31	19
E79	3646	3600	460	410	21	25	33	38	24
E79	3656	3600	560	510	30	35	45	50	41
E79	3664	3600	640	540	42	47	56	62	54
E79	3669	3600	690	580	52	57	66	73	72
E79	3677	3600	770	650	70	76	87	95	92
E79	3684	3600	840	700	88	92	108	117	135
E79	4144	4100	440	390	15	18	24	28	21
E79	4148	4100	480	430	18	22	30	36	27
E79	4158	4100	580	530	28	32	42	46	46
E79	4166	4100	660	580	40	45	52	58	60
E79	4171	4100	710	600	46	52	62	69	81
E79	4179	4100	790	680	65	70	81	88	100
E79	4188	4100	880	730	80	85	102	109	148

The suitable data in the chart are indicative not bound. Seravesi srl maintains continuously a politic improvement, therefore we reserve the right to bring changes to satisfy your application

Kw
30
35
45
60
80
90
150
30
35
45
60
80
90
150
30
35
45

60
80
90
150
30
35
45
60
80
90
150
30
35
45
60
80
90
150
30
35
45
60
80
90
150